

The DIATEST Thread Depth Gauge:
For the simultaneous gauging of thread or bore depth
and detecting of nogo gauges



A DIATEST setting gage can be used for all DIATEST TD-Gauges
A DIATEST disconnecting device including parallel bench vice
can be used for all DIATEST TD-Gauges

Thread: DIN 2282 (GO) and DIN 2284 (NOGO) Cylinder plug gauge: DIN 2248 (GO) and DIN 2249 (NOGO)

The universal system for DIN-gauges of all manufacturers

DIATEST TD-Gauge



The outstanding features of the DIATEST TD-Gauge are its suitability to be used with DIN-gauges of all manufacturers as well as the display which is always visible with resolution choices of .01 mm or .0005"



DIATEST TD-Gauge with Thread Gauge

TD-Gauge 01 (analogue only): **M2,5 to M3**

TD-Gauge 02 (digital + analogue): **M3,5 to M6**

TD-Gauge 03 (digital + analogue): **M7 to M10**

TD-Gauge 04 (digital + analogue): **M11 to M14**

TD-Gauge 05 (digital + analogue): **M16 to M18**



DIATEST TD-Gauge with Cylinder Plug Gauge

TD-Gauge 01 (analogue only): **2,0 to \leq 3,0 mm**

TD-Gauge 02 (digital + analogue): **> 3,0 to \leq 6,0 mm**

TD-Gauge 03 (digital + analogue): **> 6,0 to \leq 10,0 mm**

TD-Gauge 04 (digital + analogue): **> 10,0 to \leq 14,0 mm**

TD-Gauge 05 (digital + analogue): **> 14,0 to \leq 18,0 mm**

Analogue version also available:
Simultaneous display of pre- and post decimal point places, reading accuracy: 0,05 mm



Many special features on request: special depth stops, dirt- and air grooves, certificates for linearity, thread gages and cylinder plug gages, wireless data transmission (DIAWIRELESS),...

